

Specifications

| Model Name | | RTV400Ci | RTV500 |
|---------------------------------------|----------------------------------|---|--|
| Engine | Type | 1-cylinder, Petrol, OHC, Air-cooled, EFI | 2-cylinder, Petrol, OHC, Water-cooled, EFI |
| | Displacement | 404 cc | 456 |
| | Horsepower | 16.0 (11.9) / 4800 HP (kW) / rpm | 15.8 (11.8) / 3600 |
| Fuel tank capacity | | 20 ℓ | |
| Transmission | | CVT PLUS Continuously Variable Transmission (CVT) with Inertial Clutch | VHT PLUS Variable Hydro Transmission |
| Max. travelling speed | | 40 km/h | |
| Wheels, drive system | | 4, 4WD w/2WD selection | |
| Differential lock | | Standard; hand operated with mechanical holder | |
| Gear selection | | Hi-Lo range forward, neutral, reverse | |
| Brakes | Front / Rear | Dry-disc brakes | |
| | Parking brake | Rear wheel, hand lever | |
| Steering | | Rack & Pinion | |
| Suspension | | Independent, Mac-Pherson strut-type / Semi-independent, multi-link | |
| Dimensions | Length | 2690 mm | |
| | Width | 1390 mm | |
| | Height, overall | 1829 mm | |
| | Front tread centers | 1016 mm | |
| | Rear tread centers | 1041 mm | |
| | Wheelbase | 1800 mm | |
| | Ground clearance front/rear axle | 205 / 172 mm | |
| | Turning diameter | 7 m | |
| Max. rolling weight (towing capacity) | | 500 kg | |
| Payload capacity | | 480 kg | 430 kg |
| Weight | | 565 with ATV tires, 570 with HDWS Tyres | 615 with ATV Tires, 620 with HDWS Tyres |
| Cargo bed | Width × Length × Depth | 1032 × 856 × 290 mm | |
| | Volume | 0.25 m ³ | |
| | Bed height (unloaded) | 810 mm | |
| | Cargo bed load | 200 kg | |
| Tyres | Front | 24 × 9-12 ATV, 6PLY | |
| | | 24 × 9-12 HDWS, 6PLY | |
| | Rear | 24 × 11-12 ATV, 6PLY | |
| | | 24 × 11-12 HDWS, 6PLY | |
| Body color | | Orange, Camouflage (Realtree® Hardwoods®) | |
| Speedometer | | Opt. | |
| Front guard | | Opt. | |
| Headrest | | Opt. | |

**Realtree® is a registered trademark of Jordan Outdoor Enterprises, Ltd.

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this web site are shown with optional accessories. For off-highway use only.

©2013 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 268000 Fax (08702) 429677
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>